

making connections beautifully

Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

7G22T21

Hartland G2 | HARTLAND G2 RANGE | Toggle Switches

Primary Range Hartland G2 Insert Type In gang 20AX 2 Way Toggle Insert Colour Satin Brass EAN13 Barcode 5051164025403 Commodity Code 835363030 Luckins TSI 425822564 Dimensions(Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity	Item Image	Wiring	Dimensions
Primary Range Hartland G2 Insert Type 1 gang 20AX 2 Way Toggle Insert Colour Satin Brass EANIS Barcode 5051164025403 Commodity Code 8556330 Luckins TSI 423822564 Dimensions(Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 Sxlmm² Terminal Capacity 1 Sxlmm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 Sxlmm² Earth Terminal Capacity 1 Sxlmm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1			HARTLAND G2 T21
Insert Type 1 gang 20AX 2 Way Toggle Insert Colour Satin Brass EANI3 Barcode 5051164025403 Commodity Code 85363030 Luckins TSI 423822564 Dimensions(Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only		Description Law Service Coop in Loop Out Intermedate switching	
Insert Type	Primary Range	Hartland G2	
Insert Colour			
Commodity Code 85363030 Luckins TSI 423822564 Dimensions(Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 Sxlmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 1 5xlsmm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Luckins TSI 423822564 Dimensions(Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 2 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 2 5xl.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	EAN13 Barcode		
Luckins TSI 423822564 Dimensions(Nominal) Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 2 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 2 5xl.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 5xl.5mm² Earth Terminal Capacity 7 2x4mm² Multi-strand Earth Terminal Capacity 8 3x2.5mm² Earth Terminal Capacity 9 1x6mm² E	-		
Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 5xl.5mm² Earth Terminal Capacity 7 2x4mm² Multi-strand Earth Terminal Capacity 8 3x2.5mm² Earth Terminal Capacity 9 1x6mm² E	Dimensions(Nominal)		
Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only			
Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 1x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Current Rating		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 5x1.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Voltage		
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Farth Terminal Capacity 5 1x6mm² Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Maximum Load	20 Amp inductive	
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 5 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 5 Terminal Capacity 3 Terminal Capacity 5 Terminal	Mains Frequency	50Hz	
Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	IP Rating	IP2XD	
Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Contact Gap Minimum	3mm	
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Ix6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 1	5x1mm²	
Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 2	4x1.5mm²	
Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 3	2x2.5mm²	
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 4	2x4mm² Multi-strand	
Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Terminal Capacity 5	1x6mm²	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Ix6mm² Product Class 1 Ambient Operating Temperature Recommended Location Associated as 3	Earth Terminal Capacity 1	6x1mm²	
Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix6mm² Product Class 1 Ambient Operating Temperature Recommended Location August 2x4mm² Multi-strand Ix6mm² Must be earthed -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 2	5x1.5mm ²	
Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 3	3x2.5mm ²	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 4	2x4mm² Multi-strand	
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Earth Terminal Capacity 5	1x6mm²	
Recommended Location Internal Use Only	Product Class 1	Must be earthed	
, and the second	Ambient Operating Temperature	-5° to +40°C	-
Maximum Installation Altitude 2000m	Recommended Location	Internal Use Only	
	Maximum Installation Altitude	2000m	
Standard/Approval BS EN 60669-1	Standard/Approval	BS EN 60669-1	



Decorative Wiring Accessories • Smart Lighting Control • Wireless Audio

Registered in London No. 941624 VAT Registration No. 222 6607 84

7G22T21 - Hartland G2 Satin Brass 1 gang 20AX 2 Way Toggle Satin Brass

7G22T21 Hartland G2 | HARTLAND G2 RANGE | Toggle Switches It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Due to manufacturing processes we Illustrations and diagrams are reproduced within the limitations of cannot guarantee an exact colour Correct as at 03 May 2022 12:11 PM E&OE reproduction and printing process and match and shadings of of certain are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB